

X'Sling®

Boost your industrial performance, for the individual securing of slings, close to your workstation.

- 1** Attach your slings, chains within hand's reach.
- 2** Manage the operational status of the product.
- 3** Secure the use of the products.



**EVERYTHING
I NEED,
WHEN I
NEED IT!**

SAM'URAI®
UNITÉ DE RANGEMENT AUTOMATISÉE INTELLIGENTE

samurai-by-sam.fr

■ INNOVATIVE
■ FRENCH
■ MANUFACTURER

SAM
CRÉATEUR DE SOLUTIONS

X'Sling®

• **ANTI-FOD/FME GUARANTEE**
in your workshop



• **MANAGE CONTROL DATES**
of your equipment



• **MAINTAIN IN OPERATIONAL
CONDITION**
your harnesses and slings



• **TRACK THE DISTRIBUTION**
of these sensitive materials



• **MAINTAIN IN OPERATIONAL
CONDITION** alerts and events,
control dates, and verification
of your materials



• **SECURE YOUR PRODUCTION
AND MAINTENANCE
PROCESSES**



Let's build your 4.0 project together

SAM ASSISTANCE - SAM CONSEIL :
+33 (0)4 77 92 13 00

SAM ONLINE :
samurai-by-sam.fr

SAM'URAI®
UNITÉ DE RANGEMENT AUTOMATISÉE INTELLIGENTE

INNOVATIVE
FRENCH
MANUFACTURER

samurai-by-sam.fr



TECHNICAL SPECIFICATIONS

Access Security

- Identification by company badge on a smart unit connected to the X'Sling

Storage Unit

- 8 hooks
- Max. weight per hook: 20 kg
- Total capacity: 160 kg
- Unit to be fixed with screws on a wall (not provided)
- «Automatic» opening of hooks
- Ethernet connection

Container

- Colors: red and black
- Height: 362 mm - Width: 1123.6 mm - Depth: 157.7 mm
- Weight: 18.7 kg
- Operating temperature: -15°C / 40°C
- Set of stickers and drilling template provided.

Optional

- Anti-theft cable
- Fixing foot

Standards

2006/42/CE • EN 61000-6-4 • EN 61000-3-2
EN 61000-3-3 • EN 61000-6-2 • EN 301 489-1
EN 301 489-3 • EN 301 489-52



SAM
CRÉATEUR DE SOLUTIONS